



Full stainless steel structure  
Full mold production



Save water 30% above




Save power 25% above



Extraction reaches Max. 420G

- Advanced intelligent microprocessor
- Large display screen
- 30 programs available
- USB transfer
- Easy to program, easy to control
- Support 8 different languages



SXT-400FD/ZQ  
SXT-600FD/ZQ  
SXT-800FD/ZQ



SXT-1000FZQ  
SXT-1200FZQ



SXTQ-1200FZQ



OASIS washers are developed not only to clean, but to extend linen life, reduce water usage, and reduce utility costs, and maximize productivity. Our heavy-duty construction provides reliable operation and guarantees your washer-extractor will be in service for years to come, while our High G-Force extraction removes more water from each load, reducing energy cost, shortening drying times, thus increasing through put. The SXT series high performance washer-extractors deliver high-speed extract, an easy-to-install, freestanding design, unmatched durability and the ultimate in programmability!

## Features and Benefits

### STAINLESS STEEL CONSTRUCTION

- All metallic parts that come into contact with wash are in AISI304.
- Durable AISI304 stainless steel inner and outer drums designed for constant use.
- Front, side, and top panels are all in AISI304.

### MOLDED FABRICATION

- 80% above parts are processed by molds.
- The inner and outer drum is processed by laser.
- Achieve compact design, light but robust structure.
- Maximize the durability and longevity.

### INDEPENDENT SUSPENSION SYSTEM

- With the multi directional springs system, the machine can absorb 97% of all vibrations.
- Ensure the stability when the extract speed reaches up to max. 450G.

### DRIVE SYSTEM

- Specially made inverter, the inverter controlled motor and the matched controller programs enable the extract speed reach up to 450G.
- Advanced electronic balancing technique achieves out of balance automated load adjustment.
- Significant reduction in noise, vibration, and fatigue of the washing machine components.

### SUPER-SPEED EXTRACT

• The washers are able to quietly and gently reach extract speed up to Max. 450G. This feature benefits the laundries with less operation time, less drying-time which brings lower energy consumption and labor expense.

### PERFECT CLEANING QUALITY

• Large diameter basket with multiple ribs produces better mechanical wash action for optimum wash quality with less detergent.

- Single motor inverter drive allows programmable right wash speed for wide variety of fabrics.
- 5 automatic detergent cups turn over and flush all detergents thoroughly into the basket, no remaining lump in cups.

## INSTALLATION

- Thanks to the independent suspension system, the washers can be installed on any normal and unconventional locations with zero impact on the floor or ground.
- Optimized balance - No anchoring required.

## EASY MAINTENANCE

- All components requiring regular maintenance are easily accessible.

Model		SXT-400	SXT-600	SXT-800	SXT-1000	SXT-1200	SXTQ-1200
		Stat.	Stat.	Stat.	Stat.	Stat.	Tilt
<b>DRUM</b>							
Load Capacity	KG	40	60	80	100	120	120
Drum Volume	L	400	565	750	1000	1100	1100
Drum Depth	mm	626	620	820	746	816	816
Drum Diameter	mm	903	1078	1078	1310	1310	1310
<b>CYLINDER SPEED</b>							
Washing Speed	rpm	44	44	44	42	42	42
Spinning Speed	rpm	800	760	760	750	750	750
G-force	G	320	350	350	420	420	420
<b>CONNECTIONS</b>							
Water Inlets(2)	inch	1-1/2	1-1/2	1-1/2	2	2	2
Drain Outlet	mm	∅ 76	∅ 76	∅ 76	∅ 110x2	∅ 110x2	∅ 110x2
Steam Inlet	inch	1	1	1	1	1	1
<b>PRESSURE</b>							
Steam Pressure	mpa	0.4-0.5	0.4-0.5	0.4-0.5	0.4-0.5	0.4-0.5	0.4-0.5
Water Pressure	kgs	1.5-4	1.5-4	1.5-4	1.5-4	1.5-4	1.5-4
<b>DOOR</b>							
Door Opening	mm	∅ 690	∅ 690	∅ 690	865*834	865*834	865*834
Floor to Door	mm	982	1184	1200	1226	1226	1440
<b>POWER</b>							
Motor Power	KW	4	5.5/7.5	7.5	11	11	11
Heater Power	KW	30	30	N/A	N/A	N/A	N/A
<b>DIMENSION</b>							
Width	cm	1230	1619	1619	1770	1770	1850
Depth	cm	1370	1500	1700	1790	1860	1897
Height	cm	1735	1962	1962	2058	2058	2253
<b>WEIGHT</b>	kg	1200	1960	2600	3000	3300	3500

## PARAMETER SPECIFICATIONS

Product specifications are subject to change without prior notice.

### SXT--- SXTQ --- FD/ZQ

SXT: Stationary series

SXTQ: Tilt series

F: Inverter Drive

D: Electric heating

Z: Steam heating

Q: Fully-auto